

## EARTHMAX SR 23 - Technical Specifications



### Description

EARTHMAX SR 23 (G-2/L-2) is an All Steel radial tire specially designed for motor graders and loaders. It features superior forward and lateral traction as well as exceptional self-cleaning properties. The durable casing and the particularly cut-resistant tread provide a long service life.

### UM

International Standard

### Construction

RADIAL

### Machinery

OTR: Grader, Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	15.5 R 25
LI/SS	146 A8/169 A2

### Dimensions International Standard

Overall Width (mm)	383
Overall Diameter (mm)	1264
Static Loaded Radius (mm)	559
Rolling Circumference (mm)	3756
Rim Rec	12.00/1.3
Star Rating	*
TRA Code	G2/L2

### Load capacity (Kg)

km/h / bar	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00
40	1550	1750	2000	2180	2360	2575	2800	3000	-	-	-	-	-
10	-	-	-	-	-	-	-	-	5000	5150	5450	5600	5800

*permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*