

TR 315 - Technical Specifications



Description

TR 315 is suitable for lawn and garden, soil tillage and municipalities operations. It is ideal with implement machinery, trenchers and orchard harvesters. The TR 315 tire has a large contact area which provides excellent grip, great self-cleaning properties and outstanding stability in any condition.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Implement Machinery, Orchard Harvester, Trencher

Version	STANDARD
Type	TL
Tyre Size	26 X 12.00 - 12

Dimensions International Standard

Ply Rating	12
Section Width (mm)	308
Overall Diameter (mm)	655
Static Loaded Radius (mm)	289
Rolling Circumference (mm)	1905
Rim Rec	10½ JA
Rim Alt	8½ JA ; 9½ JA
ECE	E4-106R-002328

Load capacity (Kg)

km/h / bar	4.50
15	1600

its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..