

AS 504 - Technical Specifications



Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Telehandler, Field Trailer
Industrial: Telehandler

Version	STANDARD
Type	TL
Tyre Size	420/55 - 17

Dimensions International Standard

Ply Rating	16
Section Width (mm)	430
Overall Diameter (mm)	910
Static Loaded Radius (mm)	407
Rolling Circumference (mm)	2712
Rim Rec	13.00
ECE	E11-106R-003302

Load capacity (Kg)

km/h / bar	3.50
10 FR	4060
25 FR	3450
30 FR	3250
40 FR	2900
10 DW	2885
25 DW	2450
30 DW	2305
40 DW	2060

Printed on 24/09/2020 16:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..