

FL 630 ULTRA - Technical Specifications



Description

FL 630 ULTRA is suitable for trailers, tankers and spreaders. Thanks to its reinforced bead and the particular tread design, it is the ideal tire for multipurpose use on any kind of land or on the road. FL 630 ULTRA stands for extraordinarily reduced soil compaction.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Spreader, Tanker, Trailer

Version	STANDARD
Type	TL
Tyre Size	500/60 R22.5
LI/SS	155 D/166 A8

Dimensions International Standard

Section Width (mm)	503
Overall Diameter (mm)	1172
Static Loaded Radius (mm)	521
Rolling Circumference (mm)	3592
Rim Rec	AG 16.00
Rim Alt	15.00 ; 16.00 ; 17.00
ECE	E4-106R-001404

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1130	1310	1485	1780	2085	2385	2670	2970	3250	3530
65	1240	1435	1630	1950	2290	2610	2930	3255	3565	3875
50	1505	1740	1970	2345	2770	3160	3540	3940	4315	4690
40	1700	1965	2230	2680	3110	3560	3990	4440	4880	5300
25	1960	2270	2575	3080	3615	4110	4630	5130	5635	6125
10	2235	2585	2930	3500	4100	4700	5250	5850	6420	6975

Printed on 25/09/2020 13:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..