

## POWER TRAX HD (FL) - Technical Specifications



### Description

POWER TRAX HD is a premium bias-ply tire that is specially designed for forklift equipment in industrial applications. The deep tread, the extra thick sidewall and the tough casing provide exceptional durability minimizing the risk of punctures and accidental damages. The tire features excellent cut, chip and tear resistance suitable for rough and hard concrete surface. The specially designed rim guard ensures protection against flats and wheel damages in the rim flange area.

### UM

International Standard

### Construction

BIAS

### Machinery

Industrial: Forklift

Version	STANDARD
Type	TT
Tyre Size	18 X 7 - 8 (180/70 - 8)

### Dimensions International Standard

Ply Rating	16
Section Width (mm)	173
Overall Diameter (mm)	470
Rim Rec	4.33 R
Rim Alt	5.00 F

### Load capacity (Kg)

	km/h / bar	
		10.00
25 LOAD WHEEL		2145
25 STEER WHEEL		1650
10 OTHER VEHICLES		2145
25 OTHER VEHICLES		1650
STATIC SIDE LOADER		2490

*publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*