

MULTIMAX MP 522 - Technical Specifications



Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Compact Loader, Telehandler
Industrial: Compact Loader, Telehandler

Version	STANDARD
Type	TL
Tyre Size	400/70 R 20 IND (16.0/70 R 20)
LI/SS	149 A8/B

Dimensions International Standard

Section Width (mm)	404
Overall Diameter (mm)	1068
Static Loaded Radius (mm)	476
Rolling Circumference (mm)	3222
Rim Rec	13
Rim Alt	12 SDC; 13 SDC; 14
ECE	E4-106R-002319

Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1560	1855	2115	2405	2700	2895	3250	-	-
40	1560	1855	2115	2405	2700	2895	3250	-	-
30	1675	1985	2265	2580	2890	3100	3480	-	-
25	1735	2060	2350	2675	3000	3215	3610	-	-
10 Cyc	1905	2340	2755	3170	3610	3925	4440	4680	4875
Static	2920	3590	4225	4860	5535	6020	6805	7180	7475

Printed on 24/09/2020 10:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..