

CON STAR - Technical Specifications



Description

CON STAR is particularly suitable for compact loaders and telehandlers in agro-industrial, lifting and loading applications. It features great traction along with excellent vertical and horizontal stability. CON STAR has been made of a cut-and-chip-resistant compound contributing to an extended tire life-cycle.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Compact Loader, Telehandler
Industrial: Compact Loader, Telehandler

Version	INDUSTRIAL
Type	TL
Tyre Size	480/80 - 26 (18.4 - 26)
LI/SS	160A8

Dimensions International Standard

Section Width (mm)	490
Overall Diameter (mm)	1410
Static Loaded Radius (mm)	643
Rolling Circumference (mm)	4272
Rim Rec	DW 15 L
Rim Alt	DW 16 L
ECE	E11-106R-003033

Load capacity (Kg)

km/h / bar	3.20
40	4500

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..