

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Sprayer, Tractor, Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	280/85 R 24 (11.2 R 24)
LI/SS	115 A8/B

Dimensions International Standard

Section Width (mm)	292
Overall Diameter (mm)	1086
Static Loaded Radius (mm)	492
Rolling Circumference (mm)	3224
Rim Rec	W 10
Rim Alt	W 9
ECE	E4-106R-000611
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	670	780	890	1000	1110	1215
40	670	780	890	1000	1110	1215
30	720	840	955	1075	1190	1305
10 LT	900	1045	1190	1340	1485	1630
10 HT	720	840	955	1075	1190	1305

Printed on 22/09/2020 12:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..