

AGRIMAX TERIS - Technical Specifications



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle – also in harsh conditions and if there are stubbles in the fields.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Cotton Picker, Harvester

Version	STANDARD
Type	TL
Tyre Size	IF 580/80 R 34 CFO
LI/SS	177 D

Dimensions International Standard

Section Width (mm)	586
Overall Diameter (mm)	1792
Static Loaded Radius (mm)	810
Rolling Circumference (mm)	5422
Rim Rec	DW 20 B ; DW 20 A
Rim Alt	DW 21 A ; DW 21 B
ECE	E4-106R-001833

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
65	2705	3140	3580	4090	4530	4965	5405	5770	6355	6865	7300
50	2705	3140	3580	4090	4530	4965	5405	5770	6355	6865	7300
40	2705	3140	3580	4090	4530	4965	5405	5770	6355	6865	7300
30	2705	3140	3580	4090	4530	4965	5405	5770	6355	6865	7300
30 Cyc.	3515	4080	4655	5315	5890	6455	7025	7500	8260	8925	9490
25	2705	3140	3580	4090	4530	4965	5405	5770	6355	6865	7300
15 Cyc.	4195	4865	5550	6340	7020	7695	8380	8945	9850	10640	11315
10	2705	3140	3580	4090	4530	4965	5405	5770	6355	6865	7300

Printed on 22/09/2020 15:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..