

AGRIMAX RT 945 - Technical Specifications



Description

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Sprayer, Tractor

Version	STANDARD
Type	TL
Tyre Size	380/90 R 54 (14.9 R 54)
LI/SS	158 A8/B

Dimensions International Standard

Section Width (mm)	380
Overall Diameter (mm)	2056
Static Loaded Radius (mm)	962
Rolling Circumference (mm)	6296
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-001488
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	1955	2510	3060	3315	3615	3955	4250	-
40	1955	2510	3060	3315	3615	3955	4250	-
30	2095	2685	3280	3550	3870	4235	4550	-
10	2295	3000	3635	4335	4975	5165	5740	6375

Printed on 22/09/2020 13:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..